





PRODUCT COMPARISON INFORMATION

	Flex Trim / Ultra-Flex / Carter Millwork				Main
<u>Characteristic</u>	Flex Trim	Zzz Flex	<u>Ultra-Flex</u>	Machinable S4S	Competitor
FLEXIBILITY	© ©	000	X	X	o
PAINTABILITY	X	×	x	X	×
STAINABILITY	(a)	© ©	000		(
WEIGHT			00		
XTRULINEAR (Extended Lengths)	©	0			(
MACHINABLE			0	00	
STRENGTH	<u></u>	00	X	X	(a)
WARRANTY	Lifetime	Lifetime	1 Year	1 Year	1 Year
MOISTURE RESISTANCE	X	X	X	X	Х
INSECT RESISTENCE	X	X	X	X	Х
INTERIOR	X	X	X	X	Х
EXTERIOR	X	X	X	X	X
AVAILABILITY	UT / NC	UT / NC	UT ONLY	UT ONLY	NC/CA
# of PROFILES AVAILABLE		OVI	ER 35,000		15,000
					-1 '
	Ideal solution for most standard applications	Ideal for "extreme applications" (Very tight radius, more flexible in cold, etc)	Extremely lightweight (40-50% lighter) Pre-primed (stains better)	Okay for use with Moulders Composition more similar to wood	
KEY CHARACTERISTIC		20% more expensive than std Flex Trim	Ideal for larger profiles (due to weight) Better glue adhesion (back-sanded)	**dimension limitations: maximum 2" thick, 16" wide, 12' long minimum 1/2" thick, 1-3/4" wide, 8' long	